



Ordering Chart: Call OPW Customer Service at **800-547-9393** for complete ordering information.

Style 44 is drop tube swivel w/handle. Styles 35, 45, 55 have threaded boss. Styles 56, 58, 76, 78 have spring balance attachment lugs.

Style (Planes of Rotation)

3 4 2 0 F - 0 4 0 3

Seal Materials

- 1 - Buna-N (Standard)
- 2 - Viton®
- 3 - Teflon®
- 4 - EPT
- 5 - Food Grade Nitrile

Kalrez®, Chemraz® and other seal materials available.

Construction

- Conventional Hose Reel Swivels**
 - 26 - Aluminum Hose Reel
 - 28 - Ductile Iron Hose Reel
- Conventional Swivels**
 - 32 - Steel, High Pressure Cast
 - 33 - Bronze
 - 34 - Steel, Fabricated
 - 36 - Aluminum
 - 37 - 316 Stainless Steel, Cast
 - 38 - Ductile Iron
 - 39 - 316 Stainless Steel, Fabricated
- Endura™ Split Flange Swivels**
 - 74 - Steel Endura™ LPG Hose Reel
 - 79 - 316 SST Endura LPG Hose Reel
 - 84 - Steel Endura DSF
 - 89 - 316 SST Endura DSF

Alloy20®, Hastelloy®, Monel®, Duplex, PTFE-lined and other materials available.

End Connections

- F** - 150 lb. ASME flange both ends
- FFT** - 150 lb. ASME flange inlet x TTMA tank truck flange outlet
- FJ** - For submerged use, 150 lb. ASME flange both ends
- FO** - 150 lb. flange x female NPT threads
- FSB** - 150 lb. flange both ends, with spring balance attachment lugs
- FT** - TTMA tank truck flange both ends
- FTH** - TTMA tank truck flange both ends, with female
- VO** - Victaulic® x female NPT threads
- FTO** - TTMA tank truck flange inlet x female NPT threaded outlet
- J** - For submerged use
- LFT** - Long swivel joint with TTMA tank truck flanges
- TFT** - Female NPT threaded inlet x TTMA tank truck flange outlet
- VOG** - Female NPT threads x Victaulic® groove, hard coat anodized aluminum
- W** - Beveled for welding both ends

NO SUFFIX LETTER (S) indicates Female NPT threads both ends. 300 lb. flanges available on some models. BSPT threads available.

Size

- 007** - 3/4"
- 010** - 1"
- 012** - 1 1/4"
- 015** - 1 1/2"
- 020** - 2"
- 030** - 3"
- 040** - 4"
- 060** - 6"
- 080** - 8"
- 100** - 10"
- 120** - 12"

Availability of styles, sizes and materials may vary depending upon swivel configuration. Consult OPW Customer Service regarding your exact requirements.